

| MODEL | DRIVE | TRANSMISSION | KW/HP | Product Image |
|-------|-------|--------------|-------|---------------|
|-------|-------|--------------|-------|---------------|

B Series



| | | | |
|----------|-----|-------------|-------|
| B1181 AG | 4WD | Gear Shift | 12/16 |
| B1241 AG | 4WD | Gear Shift | 18/24 |
| B2261 AG | 4WD | Hydrostatic | 19/24 |

L Series



| | | | |
|--------------|-----|-------------|-------|
| L1361 AG | 4WD | Gear Shift | 27/36 |
| L1421 DW AG | 4WD | Gear Shift | 34/42 |
| L1421 HST AG | 4WD | Hydrostatic | 34/42 |
| L5040 AG | 4WD | Gear Shift | 39/50 |

M Series



| | | | |
|---------------|-----|-------------|-------|
| M7040 DTH | 4WD | Hyd.Shuttle | 53/70 |
| M8540 DTH | 4WD | Hyd.Shuttle | 64/58 |
| M9540 DTH | 4WD | Hyd.Shuttle | 71/95 |
| M9640 DTH CAB | 4WD | Hyd.Shuttle | 71/95 |

M Series Narrow



| | | | |
|-------------------|-----|-------------|-------|
| M7040 DTH NAR | 4WD | Hyd.Shuttle | 53/70 |
| M8540 DTH NAR | 4WD | Hyd.Shuttle | 64/85 |
| M8540 DTH CAB NAR | 4WD | Hyd.Shuttle | 64/85 |

| MODEL | DRIVE | TRANSMISSION | KW/HP | Product Image |
|-------|-------|--------------|-------|---------------|
|-------|-------|--------------|-------|---------------|

M Series



| | | | |
|---|-----|---------|--------|
| M108 | 4WD | P/Shift | 81/108 |
| M135 GX std Tyres | 4WD | P/Shift | 96/130 |
| M135 GX with Flotation tyres | 4WD | P/Shift | 96/130 |
| *M135 GX W/RTK Base Station & Auto Elec Steer | 4WD | P/Shift | 96/130 |
| *M135 GX W/RTK ISO HARNESS & Auto Elec Steer | 4WD | P/Shift | 96/130 |

TLB Series

L45



| | | | |
|---------------------------------------|-----|-------------|-------|
| B26 TLB | 4WD | Hydrostatic | 19/26 |
| L45 TLB | 4WD | Hydrostatic | 34/45 |
| EK90 EXTREME STD BUCKET | 4WD | 4F/4R | 66/90 |
| EK90 TLB EXTREME MULTI PURPOSE BUCKET | 4WD | 4F/4R | 66/90 |

RTV Series

RTV X900



| | | | |
|------------|-----|-------------|-------|
| RTV X 900 | 4WD | Hydrostatic | 19/26 |
| RTV X 1140 | 4WD | Hydrostatic | 34/45 |

Zero Turn Mowers

ZG227



| | | | |
|--------|-----|-------------|-------|
| ZG 227 | 2WD | Hydrostatic | 20/27 |
|--------|-----|-------------|-------|

| MODEL | DRIVE | TRANSMISSION | KW/HP | Product Image |
|-------|-------|--------------|-------|---------------|
|-------|-------|--------------|-------|---------------|

Excavators



| Model | Weight | Diggin Dept | Flow |
|--------------------|--------|-------------|------------|
| U17-3 M | 1800KG | 2300 MM | 45 L/MIN |
| U30-6S CANOPY | 3120KG | 2820 MM | 41 L/MIN |
| U30-6S CANOPY (AC) | 4970KG | 2820 MM | 41 L/MIN |
| U50-5S CANOPY | 4970KG | 3560 MM | 50 L?MIN |
| U50-5S CANOPY (AC) | 4865KG | 3560 MM | 50 L/MIN |
| KX80CAB-3S | 8255KG | 4600 MM | 1000 L/MIN |

EK Series



| | | | |
|---------------------|-----|---------|-------|
| EK 6045-2(8SPD) | 2WD | 8F/2R | 34/45 |
| EK 6060-2(8SPD) | 2WD | 8F/2R | 45/60 |
| EK6060-4(8SPD) | 4WD | 8F/2R | 45/60 |
| EK6075-2(8SPD) | 2WD | 8F/2R | 56/75 |
| EK6075-4(8SPD) | 4WD | 8F/2R | 56/75 |
| EK6075 PRO-2(12SPD) | 2WD | 12F/12R | 56/75 |
| EK6075 PRO-4(12SPD) | 4WD | 12F/12R | 56/75 |
| EK6090 PRO-2(12SPD) | 2WD | 12F/12R | 66/90 |
| EK6090 PRO-4(12SPD) | 4WD | 12F/12R | 66/90 |

EK Unit listed above are fitter with the following accessories as standard:

Auxilliary valve. Nose weight. Rear wheel weights (except EK 6090 X Pro), and stell canopy roof.
Machanical shuttle level on EK Pro series

